



PRODUCT INFORMATION SWAN SAND & CEMENT

PRODUCT DESCRIPTION

Swan Cement Sand and Cement is a mix of Swan GP Cement and Brickies sand. It is ready to use straight from the sack, simply mix in the desired amount of water.

SUPPLY

Swan Cement Sand and Cement is available from most retail hardware and building supply outlets and is pre-packed into easy to handle 20kg plastic sacks.

SPECIFICATION

Swan Cement Sand and Cement is blended with Type GP cement which conforms to AS3972.

APPLICATIONS

Swan Cement Sand and Cement is ideal for

- Bedding pavers, paths and stepping stones.
- Capping and filling holes in concrete walls.
- Use as a cement based mortar.

LIMITATIONS

- Do not use this product in applications requiring structural strength.
- Greater additions of water may be required depending on the soil/substrate the product is being applied to.

DIRECTIONS FOR USE

1. Place the required quantity of powder into a wheelbarrow or onto a hard non-absorbent surface.
2. Do not mix more product than can be used within one hour.
3. Add water gradually and mix thoroughly to obtain an even colour being careful not to allow any cement to wash away.
4. Use the mixed product within one hour. Do not allow to stand as reworking the mix can degrade its performance.

SUGGESTED WATER ADDITION AND YIELD

Bag Size	Max. Water	Yield/Bag	Bags per m ³
20 kg	1.5 litre	8.7 litre	115 bags

TYPICAL PROPERTIES

Approximate Mix Composition (parts by volume)	
Cement Binder	: 1 parts
Sand	: 4 parts
Compacted Density (cast)	2,100 - 2,250 kg/m ³
Powder Density	1,500 - 1,700 kg/m ³

HANDLING AND STORAGE

Manual handling of bag products without due care and attention may result in personal injury. Unless you have been trained in manual handling methods it is suggested that you share the load with another person.

Swan Cement Sand and Cement can be stored for up to six months provided it is stored in a place, off of the ground and protected from ingress of moisture. Ingress of moisture can occur due to rain, liquid spillage (on or around the product) or a high humidity climate. Such exposure will degrade the performance of the product.

SAFETY INFORMATION

For safety information refer to the Safety Data Sheet for Dry Mixed Sand and Cement Packs.

CONTACT POINTS

For further information contact the Sales and Marketing Department at:

Swan Cement Limited
Lot 242 Russell Road East
Munster WA 6166
Telephone: 08 9411 1000

Facsimile: 08 9411 1150

Web Site: <http://swancement.com.au/>

Safety Information

For safety information refer to the Safety Data Sheet for Swan Pre-Packed Products.

Swan Cement™

P O Box 38, Hamilton Hill, WA, 6163
Ph: (08) 9411 1111 Fax: (08) 9411 1120
www.swancement.com.au