



SAND & CEMENT

PRODUCT DESCRIPTION

Swan Cement Sand & Cement is a mix of Swan GP Cement and brickies sand. It is ready to use straight from the sack, simply mix in the desired amount of water.

SUPPLY

Sand & Cement is available from most retail hardware and building supply outlets and is prepacked into easy to handle 20 kg plastic sacks.

SPECIFICATION

The fine aggregate and Type GP cement used in Sand & Cement satisfies the requirements of AS 2758.1 and AS 3972 respectively.

All products are manufactured under a third party certified manufacturing and supply quality assurance system to ISO 9001 (BSI Certification No FS 604665).

APPLICATIONS

Sand & Cement is ideal for:

- Bedding pavers, paths and stepping stones.
- Capping and filling holes in concrete walls.
- Use as a cement based mortar.

LIMITATIONS

- Do not use this product in structural applications.
- Increased water additions might be necessary depending on the soil/substrate characteristics.

DIRECTIONS FOR USE

1. Place the required quantity of powder into a wheelbarrow or onto a hard non-absorbent surface.
2. Do not mix more product than can be used within one hour.
3. Add water gradually and mix thoroughly to obtain an even colour being careful not to allow any cement to wash away.
4. Use the mixed product within one hour. Do not allow to stand as reworking the mix can degrade its performance.

SUGGESTED WATER ADDITION AND YIELD

Bag size	Max. Water	Yield	Bags/m ³
20	1.5 litre	8.7 litre	115

TYPICAL PROPERTIES

Mix composition (parts by volume):	
Cement binder	- 1 part
Sand	- 4 parts
Compacted density	2,100 - 2,250 kg/m ³
Powder density	1,500 - 1,700 kg/m ³

HANDLING AND STORAGE

Manual handling of bag products without due care and attention may result in personal injury. Unless you have been trained in manual handling methods it is suggested that you share the load with another person.

Sand & Cement can be stored for 6 months in a dry place, off of the ground and protected from ingress of moisture. Ingress of moisture can occur due to rain, spillage of liquid (on or around the product) or a high humidity climate. Such exposure will degrade the performance of the product.

SAFETY INFORMATION

For safety information refer to the safety datasheet for Sand & Cement.

CONTACT POINTS

For further information contact the Sales and Marketing Department at:

Swan Cement Ltd
ABN 50 008 673 470
Lot 242 Russell Road East
Munster WA 6166

Telephone: 08 9411 1111

Email: sales@cockburncement.com.au

Web Site: www.swancement.com.au

DISCLAIMER

While the information in this Product Data Sheet has been prepared in good faith, Swan Cement Limited does not warrant that the information is accurate, complete or up to date.

Each user of any information, or any product referred to, in this Product Data Sheet must:

- Determine whether the information or product is suitable for their purpose;
 - Assess and control any risks associated with the information or product; and
 - Obtain professional advice in relation to the use of the information or product.
- Failure to do so may result in serious damage or injury.

To the extent permitted by law, Swan Cement Limited:

- Excludes all representations, warranties and guarantees in relation to any information in this Product Data Sheet; and
- Will not be liable for any direct, indirect, consequential, incidental, special or economic loss (including but not limited to any loss of actual or anticipated profits, revenue, savings, production, business, opportunity, access to markets, goodwill, reputation, publicity, or use) arising from any use of or reliance on any information in this Product Data Sheet.

The Swan Cement logo and Swan Cement are registered trademarks of Swan Cement Limited and its related entities.